


UN38.3 Lithium Battery Test Summary for 2447-3033-X20
Battery Manufacturer Ansmann AG Industriestr. 10, 97959 Assamstadt Stafford Park 12 Tel: +49 6294 4204-0 Email: info@ansmann.de
UN38.3 Test Lab Pony Testing International Group Shenzhen Co. Ltd 1F, Building A2 Jun Feng ZhongCheng ZhiZao Innovation Park HePing Peace Community FuHai Road, BaoAn District Shenzhen Guangdong China Tel: 400-819-5688 Email: pony@ponytest.com
Test Report ID MDIM2AYU537047A21
Date of Test Report 20-12-2016
Description of Battery Type: Lithium Ion Battery Pack Mass: 101g Nominal voltage: 3.6V Capacity: 6.7Ah (25.53Wh) Small rectangular (with rounded edges) shrinkwrap covered
UN38.3 Tests Performed T.1 Altitude test - PASS T.2 Thermal test - PASS T.3 Vibration - PASS T.4 Shock - PASS T.5 External short circuit - PASS T.6 Impact - PASS T.7 Overcharge - PASS T.8 Forced discharge - PASS
Edition of UN Manual of Tests and Criteria Used ST-SG-AC10-11-Rev.6
Approved by: <div style="text-align: center;">  Selke, Adrian <small>Digital unterschrieben von Selke, Adrian Datum: 2019.12.02 10:29:15 +01'00'</small> </div>